

500H WPL-DIGITAL PRINTING 12mm Waterproof Laminate

Product Specifications

Style Number	DW1207	
Construction	Laminate	
Edge Profile	Pressed Bevel	
Nominal Dimensions	9.41"wide, 59.06"long	
	US Units	Metric Units
Actual Product Width	9.41"	23.9cm
Actual Product Length	59.06"	150.0cm
AC rating	AC4	
Overall Product Thickness	1/2"	12mm
Core Thickness	4/5"	10mm
Surface Texture	Wood Grain	
Wearlayer Coating	AC4	
Non-Repeat Pattern	41 faces	
Installation Methods	floating	
Profile	Angle/tap	
Country of Origin	Made in China	
Waterproof	Yes, featuring LOTO Tech Plus waterproof technology	

Packaging

Area per Box	19.29 sqft	1.79 sqm
Pieces per Box	5 pcs	
Weight per Box	36.3 lbs	16.5 kg
Boxes per Pallet	40 boxes	



DW1207

Colors of 12mm Waterproof Laminate

DW1201 DELTA SAND



DW1202 ALPINE MIST



DW1203 SIERRA OAK



DW1204 ARCTIC FOX



DW1205 WOLF GREY



DW1206 SILK GREY



DW1207 BEDROCK



DW1208 CARLSBAD



DW1209 DUKE



Colors of 12mm Waterproof Laminate



The list of colors above complements the entire range of colors available for the current product.

Performance & certifications

Environmental Attributes:

- DDC laminate is certified to a standard that is set by the North American Laminate Flooring Association (NALFA), called the NALFA LF-01 standard. This standard requires 3rd party testing, and includes the "CARB" standard.
- High Recycled Content
- FloorScore certified, complying to strict indoor air-quality standards
- Low VOC adhesives & finishes
- Replication of natural looks using advanced printing technology
- Scratch Resistant: ScratchResist
- Steam Mop Approved: Yes
- Fade and Stain Resistant: Yes
- Can be installed on a wall: Yes

Warranties

25 Year Limited (Lifetime) Structural Warranty for WPL/WPL HD Premier

20 Year Limited Residential Wear Warranty

5 Year Limited Commercial Wear Warranty

The warranty will not cover installations practices not consistent with manufacturer's install & care guidelines.

PERFORMANCE	TEST STANDARD	REQUIREMENT	CONCLUSION
Impact Sound Insulation Class (IIC)	ASTM E492 & E989	-	76
Airborne Sound Transmission Loss Class (STC)	ASTM E90 & E413	-	73

