

Platinum Specifications

Composition	WPC (Wood Polymer Core)
Wear Layer Thickness	30mil
Plank Size	71"*8.9"
Plank Thickness	Overall Thickness 14mm (12mm core with 2mm attached cork pad)
Finish	Aluminum Oxide
Locking System	VALINGE 5G
Installation	Floating
Square feet per carton	17.47 square feet
Cartons per pallet	40 cartons
Additional Floor Benefits	Waterproof, Scratch and Stain Resistant Sound Absorbent and Slip Resistant, super matt, Antibacterial



WPC Flooring

WF1401 Chaise Tan



WF1402 Lawson Khaki



WF1403 French Oak



WF1404 Cabriole Brown



WF1405 Delfino



WF1406 Pecorino



WF1407 Morris



WF1408 Marzipan



Warranties

Residential Warranty	Lifetime Residential Wear Warranty
Commercial Warranty	25 YR Limited Light Commercial

CERTIFICATIONS

FloorScore	Certified
Greenguard Gold	Certified
CE	Certified
Indoor Air Comfort Gold	Certified

PERFORMANCE	TEST STANDARD	REQUIREMENT	CONCLUSION
Dimensional Stability	ASTM F2199	≤ 0.024" per linear foot	≤0.17mm (70 C*6h)
Curling	ASTM F2199	-	≤1mm (70 C*6h)
Resistance to Chemicals	ASTM F925	Slight change only	0
Static Coefficient of Friction	ASTM C1028	≥ 0.5 (reference)	R9
Impact Sound Insulation Class (IIC)	ASTM E492 & E989	-	68
Airborne Sound Transmission Loss Class (STC)	ASTM E90 & E413	-	68
Soluble Heavy Metals	ASTM F 963-17	-	conform
Total Lead (Pb)	CPSC-CH-E1002-08.1	-	conform
Ortho-Phthalates	CPSC-CH-C1001-09.4	-	conform
VOC Emission	CA 01350	OEHHA RELs	conform
Formaldehyde Emission	CA 01350	≤ 9 µg/m3	conform

