



Platinum Specifications

Composition	WPC (Wood Polymer Core)
Wear Layer Thickness	22mil
Plank Size	71"*8.86"
Plank Thickness	Overall Thickness 10mm (8mm core with 2mm attached IXPE pad)
Finish	Aluminum Oxide
Locking System	VALINGE 5G
Installation	Floating
Square feet per carton	21.83 square feet
Cartons per pallet	44 cartons
Additional Floor Benefits	Waterproof, Scratch and Stain Resistant Sound Absorbent and Slip Resistant, super matt, Antibacterial



WF9906

WPC Flooring

WF9901 Cypress Point



WF9902 Shinnecock Hills



WF9903 Oakmont



WF9904 Augusta



WF9905 Sand Hills



WF9906 Pebble Beach



WF9907 Fishers Island



WF9908 Sunningdale



Wood Polymer Core



TURKU

Warranties

Residential Warranty	Lifetime Residential Wear Warranty
Commercial Warranty	10 YR Limited Light Commercial

CERTIFICATIONS

FloorScore	Certified
Greenguard Gold	Certified
CE	Certified
Indoor Air Comfort Gold	Certified

PERFORMANCE	TEST STANDARD	REQUIREMENT	CONCLUSION
Dimensional Stability	ASTM F2199	$\leq 0.024"$ per linear foot	$\leq 0.17\text{mm}$ (70 °C*6h)
Curling	ASTM F2199	-	$\leq 1\text{mm}$ (70 °C*6h)
Resistance to Chemicals	ASTM F925	Slight change only	0
Static Coefficient of Friction	ASTM C1028	≥ 0.5 (reference)	R9
Impact Sound Insulation Class (IIC)	ASTM E492 & E989	-	68
Airborne Sound Transmission Loss Class (STC)	ASTM E90 & E413	-	68
Soluble Heavy Metals	ASTM F 963-17	-	conform
Total Lead (Pb)	CPSC-CH-E1002-08.1	-	conform
Ortho-Phthalates	CPSC-CH-C1001-09.4	-	conform
VOC Emission	CA 01350	OEHHA RELs	conform
Formaldehyde Emission	CA 01350	$\leq 9 \mu\text{g}/\text{m}^3$	conform



Floorscore® Certified